

OUTDOOR CURTAINS



www.coolawnings.co.nz



Outdoor Curtains are available in 6 different options - Hand Rolled, Crank Rolled, Chameleon Channel, Wire Guide, Zip Trak, Zips and Guides.

We can discuss with you the best option for your situation.

- » Cool Awnings custom-make Outdoor Curtains to fit your home or business.
- » Outdoor Curtains are made from 0.75mm fire retardant Clearglass PVC with a coloured PVC border for strength, or top quality PVC mesh.
- » We have a large range of fabric colours and styles, and will have one that suits your home
- » Our awnings are installed by our trade qualified builder and experienced awning installation team.
- » Outdoor Curtains can be controlled by hand, crank, spring or motor.
- » A flap at the bottom helps keep out wind and rain.
- » Cool Awnings Outdoor Curtains are manufactured using a high frequency welding process, and have a 5 year warranty on fabric and hardware.
- » Can be made up to 5.5m wide with a 3.5m drop.
- » Outdoor Curtains are not suitable for high wind situations.



Interest free and no repayments for 6 months.



CALL NOW for a FREE on-site measure and quote

Showroom 6 Morrin Road Panmure Auckland

Open Monday - Friday 8.30am - 5pm Saturday 10am - 1pm

Ph 09 570 6353 Fax 09 570 6354 Free phone 0800 100 266 www.coolawnings.co.nz

Hand rolled

- » Hand rolled outdoor curtains are attached at the top by a rope in an aluminum rope track.
- » They have a fabric pocket at the bottom, with a galvanized steel or aluminum tube, to allow easy rolling of the curtain up to the Velcro ties and to keep the fabric flat.
- » Stainless steel saddles with boat snaps are riveted to this bar, which attach to stainless steel ground fittings

Crank rolled

- » Utilises a 63mm roller tube, with cast aluminum wall brackets and a gearbox and crank handle.
- » They have a fabric pocket at the bottom, with a galvanized steel or aluminum tube, to keep the fabric flat.
- » Stainless steel saddles with boat snaps are riveted to this bar, which attach to stainless steel ground fittings.

Zip Track

- » Our Zip Track guided blind system is a great solution for vertical screening of cafes, patios and verandas.
- » Simple to operate - specialised spring loaded roller and aluminium side channels mean the screen glides easily, smoothly up or down and will stay in any position.
- » Bottom catches lock the screen in down position for heavier weather.
- » No zips, ropes, pulleys, bulky tracks, buckles or gaps on either side.
- » Zip track outdoor curtains run with side channels and are spring operated. The side channels are powder coated to match your home and there is a large range of fabrics available. No ground fixings are required.
- » The spline tape down each side slots into specially designed side channels that keeps the blind taut between pillars - no flapping or billowing.

Chameleon Channel Outdoor curtains

- » The Chameleon system consists of a crank rolled outdoor curtains with an aluminum channel on each side down which the fabric travels. The curtain is attached to an aluminum roller tube, with cast aluminum wall brackets and a gearbox and crank handle or Somfy motor. The side channels are either 75mm wide or 100mm wide for larger curtains.
- » The Chameleon system has an optional attractive headerbox.
- » The channels, bottom bar and headerbox are powder coated to match your home and we have a great range of fabrics available.
- » The Chameleon system has an extruded aluminium bottom bar to keep the fabric flat, which can be locked in place at various points down the channel.
- » No ground fixings are required.

Wire Guide System for Outdoor Curtains

- » The wire guide system consists of a roller tube controlled by either a motor or gearbox, and the bottom bar runs up and down the wire guides.
- » The wire guides and fittings are all high quality stainless steel.
- » Bottom fixing points can be mounted on the ground or to the wall/post on each side of the blind. We can provide an optional header box to hide and protect the fabric.
- » Recommended for mesh or acrylic fabric. It is NOT recommended for clearglass PVC.
- » Can be mounted on up to a 45 degree angle. Maximum size of the wire guide system is 6m wide x 4m drop.